



XTC C60 0w40

DESCRIPTION

XTC Synthetic Special Oil C60 0W-40 is a Premium Performance lubricant for aspirated or supercharged petrol engines and for diesel and turbo-diesel direct injection engines.

Its special completely synthetic formula allows to achieve extraordinary performances in terms of resistance to thermal decay and strength of the lubricating oil film even under the most severe working conditions, allowing to extend the oil change interval up to the maximum limit set by the manufacturer.

Its extraordinary rheological properties allow immediate lubrication at low temperature starting and, in operation, to increase the energy efficiency of the engine.

Thanks to its viscosimetric properties, XTC Synthetic Special Oil C60 0W-40 is able to improve fuel saving and at the same time reduce wear due to decrease of viscosity at high temperatures.

Thanks to the Bardahl technology and the effectiveness of the Polar Plus formula with Fullerene, XTC Synthetic Special Oil C60 0W-40 allows, on the one hand, a significant reduction in friction for the benefit of engine performance and protection of its mechanical parts, on the other hand, to keep the engine clean extending its durability in maximum efficiency.

XTC Synthetic Special Oil C60 0W-40 is suitable for high performance engines that require low viscosity lubricants.

SPECIFICATIONS

This product offers the following performance level:

ACEA	A3/B4
API	SN
MB	229.3/229.5
VW	502.00/505.00



PORSCHE	A40
RENAULT	RN0700/RN0710
FORD	937-A

PROPERTIES

- ✓ Superior wear control.
- ✓ Maximizes engine performance.
- ✓ Greater longevity and cleanliness of all engine parts.
- ✓ Easy start and immediate lubrication at very low temperatures.
- ✓ 100% synthetic formula.

TECHNICAL DATA

Viscosity at 40°C	79,8
Viscosity at 100°C	13,9
Viscosity Index	0,845
Viscosity at 40°C	180
Flash point	220
Pour Point	-52
T.B.N.	9,7

The information contained in this sheet is provided for reference only. Because of continual product development, changes may occur without prior notice. No liability for damages caused by the incompleteness or incorrectness will be accepted.

RECOMMENDATIONS

Handling : any safety information related to the handling and use of this product are gathered in the Safety Data Sheet.

Always check the manufacturer car manual before use.

Storage : it is recommended to use the product within 36 months. It should be stored in its original packaging, closed, and protected from light, humidity and excessive temperature.

REFERENCES & AVAILABILITIES

300040	24x1L
300053	60L
300054	200L



NOTHING WILL STOP YOU

SADAPS BARDAHL ADDITIVES & LUBRICANTS
Rue du Mont des Carliers, 3 ZI TOURNAI Ouest, 2
T: (+32) (0) 69 59 03 60

www.bardahl.fr
www.bardahlois.com